

INTERSECTION TRAFFIC ENGINEERING APPENDICES

APPENDIX A: LEADING AND LAGGING FLASHING GREEN ARROWS

APPENDIX B: THE CHALLENGE OF ALL-WAY STOPS

APPENDIX C: OTHER REFERENCES

APPENDIX D: MISCELLANEOUS REFERENCES

APPENDIX A: LEADING AND LAGGING FLASHING GREEN ARROWS

Once the decision to install a right turn flash is made, the question of whether the flash should be leading (before the main stage) or lagging (after the main stage) needs to be made. Choosing between lagging and leading green arrows should be based on traffic flows and safety.

A.1. RULE

For the reasons below, the following is the suggested rule:

- If the flash is needed from one side only, and the opposite right turn is possible, the flash **must always be leading**. The through green disc must appear at the same time as leading flashing green arrow from that approach (to ensure both the straight through and the right turn traffic flows are not confused by what would otherwise be an unexpected sequence).
- **In all other cases, the flash should be lagging.**

A.2. REASONS FOR LAGGING GREEN FLASHES

The reasons why a lagging green arrow is better than a leading green arrow, where there is no opposing unprotected right turn, are:

A.2.1. LAG GREEN COMPLIES WITH THE RULE OF THE ROAD

The rule of the road is that right turners give way to traffic from opposing directions. It is of course extremely important from a safety point of view that motorists comply with this rule. It makes sense therefore that a lagging green flash, which gives priority in accordance with this rule, should be preferred. A leading right turn arrow allows right turning to take place before opposing traffic moves, hence violates this rule. For this reason, leading greens should be limited only to where a lagging green is not permitted.

A.2.2. LAG GREEN IMPROVES TURNING SAFETY

This is a difficult area to research, but other than situations involving the “yellow trap”, it is usually found that lagging green is safer. The Purdue University 1989 study found “*that, in general, lagging sequences at selected types of intersections can provide safety and delay advantages over the (more common in Indiana) leading sequences*”.

Nowhere in the literature was it found that a leading green was safer, despite the alleged advantages of:

- opposing traffic is stopped when the turn is executed;

- most of the turns take place before the main stage and therefore less turners need to take gaps.

Counter arguments are that with a lagging flash:

- turners will not assume opposing vehicles will stop but will wait until they do;
- turners are not pressured to take gaps because they know the flash will follow.

A.2.3. LAG GREEN IMPROVES PEDESTRIAN SAFETY

There is consensus that lagging green is safer for pedestrians, e.g. *“An advantage of the lagging right-turn phase is that it provides significantly better separation between right-turning vehicles and pedestrians. This is a particularly important advantage in areas with high pedestrian volumes”* (SA Road Traffic Signs Manual).

A.2.4. LAG GREEN MEETS USER EXPECTATIONS

Drivers and pedestrians waiting at a red signal will often observe the signal on the cross road and expect to get a green signal when the cross-road signal goes red (this may not be ideal, but it is a fact). A leading green arrow gives rise to false starts when the expected green is not given and could lead to collisions.

Furthermore, a driver in a straight or left turning lane does not expect a vehicle in the adjacent right turn lane to get a green signal before him/her, a situation occurring when a leading green is displayed before the main stage. To avoid through drivers proceeding at the same time as right turners in error, if leading right turn flash is given, the green through disc signal should be shown simultaneously.

A.2.5. LAG GREEN ELIMINATES HAZARDOUS LATE TURNS

Motorists turning right at a leading green often continue turning in front of oncoming vehicles even after the termination of the yellow arrow. This aggressive behaviour commonly results in equally aggressive behaviour from motorists on the opposite side who start moving into the intersection as soon as the green for them is displayed. This behaviour can be regularly observed and can result in crashes.

A.2.6. LAG GREEN INCREASES CAPACITY

The most difficult movement at an intersection and the movement with the lowest capacity is the right turn. In the case of a lagging green arrow, motorists move into the intersection and wait for

an opportunity to turn right. As soon as there is a suitable gap, or as soon as the opposing green terminates, they are ready to turn and efficiently use the available time. The front vehicles can often start turning before the flash even begins.

With a leading right turn arrow, right turning motorists are waiting back at the stop line when the arrow starts. At the commencement of the flash, they must observe and react to the (often unexpected) arrow, proceed into the intersection, check that the opposing vehicles are not moving and then only make the turn. Sometimes, especially if they are not aware of, or are not expecting, the leading arrow, there can be additional delay before the motorist realizes (usually by the person behind hooting) that he/she has the priority.

In their paper, “The Effect of a Leading Green Phase on the Start-up Lost Time of Opposing Vehicles” delivered at the SATC 2002, Bester & Varndell showed that the start-up lost time of opposing vehicles was significantly increased when using a leading green. At an intersection in Stellenbosch, it was estimated that an approach could lose up to 13 minutes over a full day due to a leading green. It was however pointed out that some of this lost capacity was regained at the end of the main green through cycle when right turners can utilize the inter-green.

Furthermore, because of the greater turning efficiency, lagging greens can be kept quite short when traffic flows allow. A lagging green can be as little as four or even three seconds long while a leading green should be a minimum of seven seconds to allow for the starting delays.

A.2.7. LAG GREEN IMPROVES THE EFFICIENCY OF VEHICLE ACTUATED SIGNALS

If vehicle-actuated control is used at a signalized intersection, a lagging arrow is more efficient. The right-turn phase is only called if a vehicle is detected behind the stop line waiting to turn at the end of the stage. The lagging arrow is therefore only needed if there are right-turners who could not accept gaps or use the inter-green during the permitted phase and are still waiting to execute the right turn. In contrast, the leading arrow will almost always be called at the start of the main green phase because vehicles will have arrived during the red. The signal controller does not know whether these right-turners will be able to accept gaps during the following phase and hence the flash is given. To partially overcome this problem with leading greens, the detector loop is often placed around 10m behind the stop line.

A.2.8. LAG GREEN IS MORE EFFICIENT WHEN FLOWS ARE BALANCED

If the right turn volumes on opposite sides both require a protected phase, it is preferable and more efficient to use a lagging green, due to the scenarios described above.

A.3. ADVANTAGES OF LEADING GREEN FLASHES

The circumstances under which a leading green arrow is preferred are:

A.3.1. LEAD GREEN AVOIDS THE “YELLOW TRAP”

Lagging right turn green flashes running with through movements from one side only at junctions where the opposite right turn is possible (a situation known as the right turn or yellow trap) is extremely dangerous and is not permitted.

The yellow trap occurs when right turning vehicles opposite a lag flash on the other side move into the intersection and wait to turn during the permissive only (no lag flash) “main” phase. Those vehicles see a yellow followed by a red disc signal. As they are now ‘stranded’, or ‘trapped’ within the intersection, they will try to clear by turning right in the face of oncoming traffic, not realizing that vehicles coming from the opposite side have a green disc signal. A lagging right turn green and through from one side only is therefore never allowed when right turns from both sides are permitted.

This problem does not arise at T-junctions, diamond interchanges, or cross-junctions where the cross-road is one-way so here the lagging green is again preferred.

A.3.2. LEAD GREEN CATERS FOR UNBALANCED FLOWS

It is a common occurrence, especially during peak periods, that due to tidal flows the majority of through and right turn traffic approaches from the same side of the intersection. In these cases, it is advantageous to be able to display the through green and protected right turn flash at the same time while the opposite side is stopped.

This is the major reason for using leading greens.

A.3.3. LEAD GREEN ALLOWS FOR SHARED LANES AND SHORTER AUXILIARY LANES

In cases where right-turners share lanes with other movements (combined straight and right lane marking) or the auxiliary lane is very short, a leading arrow is preferable. The right-turners in the shared lane or overflowing from the short right turn lane will be able to turn unopposed at the start of the through green, and do not need to wait for gaps in opposing traffic; hence they do not delay through movements when the green signal begins. The likelihood of right turners delaying through vehicles later in the cycle is also reduced, as it is hoped that the majority of right turners will have been catered for during the protected phase.

A.3.4. LEAD GREEN ALLOWS PHASE SKIPPING

It is sometimes desirable to have the protected right turn phase running during peak periods only. During off-peak periods, the reduced number of right turners will clear during the permitted phase. With a leading green, skipping the phase when it is not needed is less likely to lead to problems.

With a lagging green, motorists may not wish to take gaps and might wait for the protected phase to begin. When this phase is skipped, they are ‘stranded’ in the middle of the intersection. While this can still happen in the leading green case with the stranger who observes the right turn head and expects a protected phase, it is less likely to occur.

In general, however, because of the confusion that it creates, it is not recommended that phases are skipped.

A.3.5. LEAD GREEN ALLOWS PHASE ROTATION

A further advantage of leading green is that can be rotated from one side of the intersection to the other to cater for changing direction of higher demand flows. It may be desirable to have the protected phase on opposite sides of the intersection during AM and PM peak periods for example. This of course is not necessary with lagging greens which serve both sides, neither is phase skipping necessary, but that is only the case when flows are balanced.

A.4. SIGNAL CO-ORDINATION

In certain instances, the green wave in a co-ordinated signal system can be affected by whether the flash is displayed before or after the main phase, especially if the intersection involved is a T-junction. While this is unlikely to be a determining factor, it should be noted that either a leading or lagging green could be fitted into the progression scheme on an arterial. These situations need to be considered on their merits when the co-ordination plan is prepared.

A.5. CONCLUSION

To provide for national consistency, standardization and safety when determining whether leading or lagging right turn flashes are installed, the following simple rule is proposed:

- If one side only and the opposite right turn is possible, the flash must be leading.
- In all other cases it should be lagging.

A further consideration is that when a protected right turn phase is introduced, especially a lagging phase, it should preferably be shown all day (not skipped).

(This paper was edited from a paper by the same author dated 22 May 2003.)

B. APPENDIX B: THE CHALLENGE OF ALL-WAY STOPS

B.1. INTRODUCTION

Certain authorities have chosen to erect Stop signs on all approaches to an intersection. This results in the all-way Stop or 4-way Stop as it is popularly known.

Various reasons for the introduction of all-way Stops are given, usually perceived or predicted accident problems, or to force vehicles to use other routes, or sometimes to prevent speeding (traffic calming). In many instances public pressure is brought to bear on the local authority to arbitrarily erect Stop signs and this pressure too has been given as a reason for installing all-way Stops.

The professional traffic engineering fraternity generally does not support all-way Stops for justifiable reasons. This paper examines the role of all-way Stops, their effectiveness, and possible alternatives. It also proposes conditions for the installation of yield and stop signs in general.

B.2. ADVANTAGES AND DISADVANTAGES

The following are the claimed advantages and disadvantages of all-way Stops:

B.2.1. ADVANTAGES

- Causes vehicles to seek other routes;
- Reduces collision risk;
- Reduces speeding;
- Assists difficult turning manoeuvres;
- Can resolve poor sight distance problems;
- Pedestrians are assisted;
- Can be used temporarily where traffic signals are warranted;
- Acceptable to public and politicians.

B.2.2. DISADVANTAGES

- Full stop illegally ignored by majority of motorists;
- Respect for Stop control is reduced, reducing safety at other intersections;
- Leads to flouting of the law;

- Enforcement is resented and often Traffic Officers are reluctant to enforce the clearly unreasonable restriction;
- Creates more (deliberate and unnecessary) delay than any other form of control;
- Reduces capacity of the intersection;
- Cost of delay and wasted fuel outweighs alleged and unproven accident benefits;
- Confusing because right of way is not well defined;
- Very dangerous / impossible to restore normal priority control;
- Speeds between intersections can increase;
- Contributor to driver aggression, or road rage (the opposite of traffic calming);
- Can cause traffic to divert to less favourable routes resulting in demands for all-way Stops on those routes too;
- Inflexible; applies for 24 hours a day.

B.3. ADDITIONAL CONSIDERATIONS

The practice of installing all-way Stops has escalated in many of the municipal areas in South Africa. The standard Stop sign is simply erected on all approaches to the intersection, even though the sign is now changed in meaning and the expected motorist response must change too. In most instances, motorists are left to pick up subtle clues to decide how to treat the sign.

The violation rate at all-way Stops can reach ninety per cent (CSIR 1980 unpublished study plus site observations). Certain enforcement authorities use this fact as a ready source of easy revenue.

Right of way, while supposedly first come – first served, is not well defined at an all-way Stop. Sometimes vehicles on the major road believe they have priority over a minor cross street and proceed even if the cross-road vehicle arrived first. When there is a queue and it is not clear who arrived first, there is further confusion, especially on wide intersections.

Some drivers are either overly courteous or excessively cautious and wait regardless, even for those vehicles that clearly arrive after them, hence reducing capacity further and delaying following vehicles. Some motorists wait unnecessarily for all cross traffic to come to a complete stop (or do not realize it is an all-way Stop) before proceeding. Others treat service on a push-in basis, even if it means proceeding in the path of opposing traffic or following the vehicle in front without stopping or waiting.

All methods are generally unsatisfactory, and all violate the proper principle of the Stop sign which is that motorists waiting at the sign must not proceed until the intersection is clear of approaching vehicles that might cross their path.

Motorists accustomed to proceeding in the face of oncoming traffic, as is the procedure at an all-way Stop sign, have caused some catastrophic crashes when they misconstrue a two-way Stop as an all-way Stop somewhere else. The same problem arises when all-way Stops have been reconverted to two-way control and motorists at the Stop street do not stop or wait for cross traffic.

The latter problem, changing all-way Stops back to two-way is dangerous because, after removal of the main road Stop signs, motorists at the Stop on the side street see a car approaching but proceed without realizing the approaching vehicle now has the right of way. This problem is so serious that removing an all-way Stop is seldom attempted, even when the original conditions necessitating its existence no longer apply. In the late 1980's, the CSIR National Institute of Transport and Road Research did some research into ways of overcoming this but results were inconclusive, and the research was stopped.

There is also the "halo effect" to contend with, when motorists accustomed to all-way Stops pull off inadvertently at two-way Stops. In these cases, the two-way Stop is blamed for causing the accident when in fact the all-way Stop, with its apparently lower crash rate, is the cause of the crash remote from its location. Crashes tend to migrate away from the all-way Stop to other intersections.

B.4. ALTERNATIVES TO ALL-WAY STOP SIGNS

In the author's opinion all-way Stops should be banned in urban areas. Two alternatives are therefore suggested.

The best and ultimate alternative to an all-way Stop is to replace it with a mini-circle. The mini-circle is an all-way Yield and hence replicates the behaviour of most motorists at an all-way Stop. The mini-circle therefore legalizes the movements that most motorists practice.

In addition, given its small size, the mini-circle will also operate on a first come – first served basis. Furthermore, it has all the alleged advantages of an all-way Stop, such as reducing speeding and traffic calming, and has none of the disadvantages.

If a mini-circle is not adopted, then the standard Stop sign should never be allowed to be displayed at an all-way Stop. Because the behaviour expected from the driver changes and because the rules of conduct at all-way Stops are different, the sign should not look like a Stop sign. Adding a 3 or 4 below is also inadequate; a new sign is therefore required.

Two suggestions are:

- retain the existing octagonal shape but replace the word STOP with a 3 or 4.
- replace the octagon with a red circular sign with 3 or 4 in white.

Both suggestions comply with the regulatory colours and sign matrix, however the second is more distinctively different and preferred.

The new sign would achieve three objectives:

1. It alerts the motorist to an all-way Stop situation;
2. It can be defined differently from the standard Stop sign to cater for the different motorist behaviour expected;
3. It can later be removed and replaced with a standard Stop or other sign, which helps alert the motorist to the changed condition.

In addition, the law should be amended to require vehicles to yield, not stop at the new sign.

B.5. WARRANTS FOR ALL-WAY STOPS

B.5.1. INTRODUCTION

All-way Stop signs are allowed by some agencies in the following “non-standard” situations:

1. As a speed control measure;
2. To discourage use of a street;
3. When approach speeds to an intersection are in excess of 64 km/h (40mph);
4. To protect school crossings.

A study by the CSIR in the 1970's found no international agreement on warrants for Stops and all-way Stops, although accident experience appeared frequently.

B.5.2. MUTCD WARRANT

Only the USA specifies an all-way Stop warrant, as follows:

1. Where traffic signals are warranted and urgently needed, the all-way Stop is an interim measure that can be installed quickly to control traffic while arrangements are being made for the signal installation.
2. An accident problem, as indicated by five or more reported accidents of a type susceptible to correction by an all-way Stop installation in a twelve-month period. Such accidents include right and left turn collisions as well as right angle collisions.
3. Minimum traffic volumes:
 - (a) The total vehicular volume entering the intersection from all approaches must average at least 500 vehicles per hour for any 8 hours of an average day, and
 - (b) The combined vehicular and pedestrian volume from the minor street or highway must average at least 200 units per hour for the same 8 hours, with an average delay to minor street vehicular traffic of at least 30 seconds per vehicle during the maximum hour, but

(c) When the 85-percentile approach speed of the major street traffic exceeds 40 miles per hour (64 km/h), the minimum vehicular volume warrant is 70% of the above requirements.

B.5.3. STOP SIGNS AS A SPEED CONTROL DEVICE

The MUTCD (USA) specifically states that Stop signs should not be used to control speeds. However, local authorities regularly receive requests for Stop signs to control speed.

Conceptually it appears obvious that Stop signs will reduce vehicle speeds. A study done in Michigan shows however that not only are Stop signs ineffective in this respect, but they are frequently ignored. The results at four study sites in residential areas in Michigan found that there was a tendency for mid-block speeds to slightly increase after Stops were installed but this was not significant. Only one quarter of motorists obeyed the Stop sign.

B.5.4. ALL-WAY STOP SIGNS AS A SAFETY DEVICE

Studies at several locations have revealed that all-way Stops provide greater safety than traffic signals when volumes are low. Volumes on the minor streets must however be at least 35% of that on the major street as intersections with ratios less than that indicate sharp increases in accident rate.

It was also found that excessive use of four-way Stops where two-way Stops were adequate also can result in sharp increases in accident rates. It was proposed therefore to use the lesser control unless found to be inadequate.

APPENDIX C: OTHER REFERENCES

The references below are not directly quoted in this report but were used while preparing the source documents. These include Google searches.

Lagging v. Leading Green Flashes

Hummer, JE, Montgomery, RE, and Sinha KC, [1989] *An Evaluation of Leading Versus Lagging Left Turn Signal Phasing*, Purdue University, Joint Highway Research Project FHWA/In/Jhrp-89/17.

Robinson, Larry, [2016] *Leading and Lagging: Left Turn Signals Compared. Now that the yellow trap problem can be removed, which is better?* [midimagic.sgc-hosting.com / ledorlag.htm](http://midimagic.sgc-hosting.com/ledorlag.htm).

Vance, Steven, [2014] *Lagging Left Turns would improve Pedestrian Safety at Complex Intersections*, Streets Blog Chicago, September 16, 2014

Zhou, Xin (Doris) [2013] *Leading versus Lagging Protected-only Left Turn Phasing in a Coordinated System*, Northeastern University, CIVE 7380 Traffic Performance Models, Traffic Simulation, and Advanced Traffic Control, 2013.

PhD References; Sampson JD, Warrants for Traffic Signals, 1971

Akcelik, R. [1981a] Fuel efficiency and other objectives in traffic system management, **Traffic Engineering and Control**, vol.21, February 1981, pp.54-65.

Akcelik, R. [1981b] **Traffic Signals: Capacity and Timing Analysis**, Australian Road Research Board, Research Report 123, March 1981.

American Association of State Highway Officials (AASHO) [1957] **A Policy on Arterial Highways in Urban Areas**, (Red Book), Washington D.C., 1957.

Atkins, S.T. [1984] Why value travel time? The case against, **Highways and Transportation**, The Journal of the Institution of Highways and Transportation, United Kingdom, July 1984, pp.2-7.

Baerwald, J.E. [1967] Why aren't traffic engineering decisions made by professionals? **Traffic Engineering**, vol.37, no.7, April 1967, p.43.

Barbaresso J.C. [1975] Flashing signal accident evaluation, **Transportation Research Record** **956**, 1984, pp.25-29.

Bauer, C.S. [1975] Some energy considerations in traffic signal timing, **Traffic Engineering**, vol.45, no.2, February 1975, pp.19-25.

Bleyl, R. [1963] A method for estimating the satisfaction of traffic signal warrants based upon ADT volumes, **Traffic Engineering**, vol.34, no.1, October 1963, p.47.

Blumenfeld, D.E. and Weiss, G.H. [1979] The effects of gap acceptance criteria on merging delay and capacity at an uncontrolled junction, **Traffic Engineering and Control**, vol.20, no.1, January 1979, p.16.

Box, P.C. and Alroth, W.A. [1967a, 1967b, 1968] Warrants for traffic control signals, **Traffic Engineering**,

Part I, vol.38, no.2, November 1967, pp.32-41.

Part II, vol.38, no.3, December 1967, pp.22-29.

Part III, vol.38, no.4, January 1968, pp.14-21.

Brown, R.J. [1972], The **Identification and Improvement of Accident Black Spots**, CSIR Technical Manual K21, Pretoria, 1972.

Brown, R.J. and Sampson J.D. [1982] Twenty-one years of traffic engineering in Johannesburg, **Traffic Engineering and Control**, May 1982.

Burrough B.L. [1988] Traffic signals: warrants, **Seminar on New Traffic Signs**, Pretoria, 16-18 May, 1988.

Cameron, Ronald M. [1977] Pedestrian volume characteristics, **Traffic Engineering**, January 1977, pp.36-37.

Carll, R.R. and Homburger, W.S. [1962] Some **Characteristics of Peak Period Traffic**, Highway Research Board Paper, January 1962.

Clement J.P. [1981] Traffic signal warrants - Time for a change? **ITE Journal**, June 1981, pp. 69-71.

Clyde M.N. [1964] Michigan study indicates signals increase accidents, **Traffic Engineering**, vol.35, no.2, November 1964, p.32.

Committee on Warrants for Four-way Stop Signs [1960] Traffic control warrant research, **Traffic Engineering**, vol.30, no.6, March 1960, p.45.

Conner, Robert E. [1971] The 1970 edition of the Manual on Uniform Traffic Control Devices, **Traffic Engineering**, vol.41, no.8, May 1971, p.5.

Cooper, D.F., Storr, P.A. and Wennell J. [1977] Traffic studies at T-junctions: 4. The effect of speed on gap acceptance and conflict rate, **Traffic Engineering and Control**, vol.18, no.3, March 1977, p.110.

Courage, K.G. and Parapar, S.M. [1975] Delay and fuel consumption at traffic signals, **Traffic Engineering**, vol.45, no.11, November 1975, pp.23-27.

Dale, C.W. [1966] A cost analysis of intersection traffic controls, **Traffic Engineering**, vol.36, no.8, May 1966, pp.45-50.

De Leuw Cather and Company [1964] **Effect of Control Devices on Traffic Operations - Interim Report**, NCHRP Report 11, Highway Research Board, 1964.

De Leuw Cather [1985a] **Proposed New Traffic Volume and Delay Warrants for Vehicular Control Signals**, CSRA/CUTA Road Signs Subcommittee, Department of Transport, Pretoria, September 1985.

De Leuw Cather [1985b] **Warrants for Four-way Stops**, CSRA/CUTA Road Signs Subcommittee, Department of Transport, Pretoria, 1985.

Demetsky M.J. and Moreno L.E. [1985] Flashing signals in peak periods, **Transportation Quarterly**, vol.39, no.1, January 1985, pp.151-166.

Desrosiers, R.D. [1966] Gap utilization - A warrant for traffic signal control, **Traffic Engineering**, vol.37, no.3, December 1966, p.21.

Division of Roads and Transport Technology [1988] **Accident Costs**, CSIR, 1988.

Drew, Donald R. [1968] **Traffic Flow Theory and Control**, McGraw-Hill, 1968.

Exter, J.O. [1976] **Introduction to Traffic Signal Control: A Literature Survey**, NITRR, RT/18/76, CSIR, South Africa, September 1976 (Restricted).

Fieldwick, Roger [1986] **The Rural Speed Limit and Traffic Accidents**, MSc Dissertation, University of the Witwatersrand, 1986.

Gerlough, D.L. and Wagner, F.A. [1967] Improved **Criteria for Traffic Signals at Individual Intersections**, NCHRP Report 32, Highway Research Board, 1967.

Gerlough, D.L. and Huber, M.S. [1975] **Traffic Flow Theory: A Monograph**, Transportation Research Board Special Report 165, Washington D.C., 1975.

Gorton, D.F. [1976] Intersection **Traffic Control for the Improvement of Capacity: An Investigation of Warrants**, National Institute for Transport and Road Research, CSIR Report RT/12/76, Pretoria, September 1976 (Restricted).

Grunschlag, D.M. [1973] Traffic control devices: Discretion in administration process, **Traffic Engineering**, vol.43, no.8, May 1973, p.28.

Guell, David L. [1982] Traffic Signals at New and Rebuilt Intersections, **Transportation Engineering Journal**, vol.108, no.TE4, July 1982, pp.419-427.

Gurnett, G.B. [1972] LA County study of 24-hour operation at pretimed signals, **Traffic Engineering**, vol.42, no.8, May 1972, p.42.

Hakkert, A.S. and Mahalel, D. [1978] The effect of traffic signals on accidents with special reference to the introduction of a blinking green phase, **Traffic Engineering and Control**, vol.19, no.5, May 1978, pp.212-215.

Heathington, K.W. and Jones, A.D. [1966] An analysis of peak period freeway volume characteristics, **Traffic Engineering**, vol.36, no.8, May 1966, p.34.

Henry, R.D., Calhoun, J.H.L., Pfefer, R.C. and Seyfried, R.K. [1982] **Peak - Hour Traffic Signal Warrant**, NCHRP Report 249, Transportation Research Board, Washington D.C., September 1982.

Hensley, M.J. and Volk, W.N. [1966] What revisions are needed in manual signal sections?, **Traffic Engineering**, vol.36, no.9, June 1966, p.59.

Hewitt R.H. [1985] A comparison between some methods of measuring critical gap, **Traffic Engineering and Control**, January 1985, pp.13-22

Highway Research Board [1965] **Highway Capacity Manual**, HRB Special Report 87, National Academy of Sciences, National Research Council, 1965. (see also Transportation Research Board [1985].)

Hobbs, F.D. [1974] **Traffic Planning and Engineering**, Pergamon Press, Oxford, 1974.

Huddart, K.W. [1980] Australian **Traffic Signalling**, ARR No 113, Australia, December 1980.

Institute of Transportation Engineers (ITE) [1982] **Transportation and Traffic Engineering Handbook**, 2nd ed., Prentice Hall, United States, 1982 (also early edition 1976).

ITE Technical Committee 4A-20 [1984] Traffic engineering practices in developing countries, **Institute of Transportation Engineers Journal**, November 1984.

International Road Federation [1980] World **Road Statistics**, 1980 edition.

Johannesburg City Engineer's Department correspondence and records, Information Processing, Civic Centre, Braamfontein, Johannesburg.

Kennedy, Norman, Kell, James and Homburger, Wolfgang [1973] **Fundamentals of Traffic Engineering**, 8th ed., Institute of Transportation and Traffic Engineering, University of California, Berkeley, 1973.

Kiln, J. [1988] **SIMTRA: Microscopic Simulation of Traffic Flow at Isolated Intersections: An Evaluation**, Research Report RT/119, DRATT, CSIR, February 1988.

Kirby R.F., Sayeg P.J. and Fehon K.J. [1986] Traffic management in Metro Manila: 2. Specifying traffic management measures, **Traffic Engineering and Control**, January 1986, pp.332-338.

Knox, D.W. and Waldron, R.J. [1972] Traffic signal warrants and priorities, **Australian Road Research Board Proceedings**, vol.6, part 3, 1972, pp.144-159.

Lalani, Nazir [1983] Street classification guides urban development, **American City and County**, April 1983, p.30.

Lay M.G. [1984] Traffic **Signals**, Australian Road Research, vol.1A, no.3, September 1984.

Leisch, J.E., Pfefer, R.C. and Moran, P.J. [1967] Effect of **Control Devices on Traffic Operations**, NCHRP Report 41, Highway Research Board, 1967.

Macnee, W.Q. [1960] Uniform traffic control devices for Canada, **Traffic Engineering**, vol.30, no.11, August 1960, p.19.

Mahalel D. and Peled A. [1984] A safety and environmental evaluation of traffic signal operation at off-peak hours, **Traffic Engineering and Control**, February 1984, pp.79-81.

Massey, S.A. [1962] Mathematical determination of warrants for pedestrian crossings, **Traffic Engineering**, vol.32, no.12, September 1962, p.19.

- Matson, Smith and Hurd [1955] Traffic **Engineering**, McGraw-Hill, New York, 1955.
- Mellors, A.R. [1976] Which **Form of Control to Use at a Road Junction**, Department of the Environment, UK, circa 1976, pp.29-34.
- Michael, H.L. [1980] Opportunities in transportation engineering funding and intersection management, **ITE Journal**, vol.50, no.3, March 1980, p.14.
- Muellar, E.A. [1970] Aspects of the history of traffic signals, **IEEE Transactions on Vehicular Technology**, vol. VT-19, no.1, February 1970.
- MUTCD [1986] see United States Department of Transportation [1986]
- National Advisory Committee [1960] see Committee on Warrants for Four-Way Stop Signs [1960].
- National Institute of Transport and Road Research (NITRR) [1979] The costs of road traffic congestion, **Transport and Road Digest**, CSIR, Pretoria, April 1979.
- Neudorff, L.G. [1978] Relationship between the removal of traffic signals and intersection accidents, **Transportation Engineering**, vol.48, no.3, March 1978, p.16.
- Neudorff, L.G. [1985] Gap-based criteria for signal warrants, **ITE Journal**, February 1985, pp.15-18.
- Oppenlander J.C. [1983] Continuous warrants for traffic signals, **ITE Journal**, May 1983, p.23.
- Pretty R.L. [1983] Alternative methods of intersection control subject to warrants, **Traffic Engineering and Control**, June/July 1983, pp.296-300.
- Ribbens H. and Brafman G. [1981] Proposed **Warrants for South African Mid-Block Pedestrian Crossings**, Technical Report RF/2/81, NITRR, CSIR, May 1981.
- Roads and Transportation Association of Canada [1976] Council on Uniform Traffic Control Devices for Canada, **Manual of Uniform Traffic Control Devices for Canada**, 3rd ed., Ottawa, 1976.
- Robertson D.I. [1975] The use of the TRRL TRANSYT method, **Traffic Engineering and Control**, December 1985, pp.562-564.
- Sampson, J.D. and Brett M. [1979] **TRANSYT in the CBD and Braamfontein**, Johannesburg City Engineer's Department internal report, 1979.

Sampson, J.D. [1983] Traffic flow variations in urban areas, **Proceedings of the Annual Transportation Convention**, Pretoria, 1983.

Sampson, J.D. [1984] Traffic accident variations, **Proceedings of the Annual Transportation Convention**, Pretoria, 1984.

Sampson, J.D. [1985] **Growth of Signals and Population in Johannesburg**, Unpublished personal notes, 1985.

SARTSM [1986] see South Africa CSRA/CUTA Road Signs Subcommittee, 1986.

Savage W.K. [1985] Traffic signal warrant "P" (Political) - A case study, **ITE Journal**, January 1985, pp.22-24.

Sessions, Gordon M. [1971] **Traffic Devices: Historical Aspects Thereof**, The Institute of Traffic Engineers, Washington D.C., 1971.

Skinner D.G. and Arnott-Job P.J. [1981] Variations in South African road accidents 1965 - 1980, **Proceedings of the Annual Transportation Convention**, Pretoria, 1981.

Slavik, Martin [1982] PhD **Thesis**, University of Pretoria, 1982

Slavik M.M. [1985] **Crossing Traffic Streams Without Control**, Bruinette, Kruger and Stoffberg, Pretoria, February 1985.

Smith E. [1970] Design capacity for urban roads, **Traffic Engineering and Control**, August 1970, pp.182-195.

Snelson, P. [1977] Criteria for cycle signal installation, **Traffic Engineering and Control**, vol.18, no.11, November 1977, p.527.

South Africa [1966] **Road Traffic Ordinance of the Transvaal (Ord. 21 of 1966) and Regulations**, Lex Patria Publishers (as revised 1988).

South Africa CSRA/CUTA Road Signs Subcommittee [1986] **South African Road Traffic Signs Manual** (SARTSM), 2nd ed., CSIR, Pretoria, South Africa, 1982 as revised March 1986.

Strok, W. [1962] Warrants for school crosswalks, **Traffic Engineering**, vol.32, no.8, May 1962, p.16.

Tarnoff, P.J. and Parsonson, P.S. [1981] **Selecting Traffic Signal Control at Individual Intersections**, NCHRP Report 233, Transportation Research Board, Washington D.C., June 1981.

Texas Department of Transportation [1980] **Manual on Uniform Traffic Control Devices**, Texas, 1980, pp.4C-1 to 4C-7.5.

Todd, K. [1976] Intersections: Is the traffic system safe?, **Traffic Engineering**, vol.46, no.8, August 1976, pp.31-35.

Todd, K. [1982] Traffic signal warrants: The controversy that never ends, **American City and Country**, December 1982, pp.25-27.

Todd K. [1987] Traffic regulation and public policy, **Transportation Quarterly**, vol.41, no.4, October 1987, pp.477-502.

Transportation Research Board [1976] Accidents in urban and rural areas, **Transportation Research Record 601**, 1976, p.81.

Transportation Research Board [1985] **Highway Capacity Manual**, TRB Special Report 209, National Research Council, Washington D.C., 1985.

TRB [1986] Accidents at flashing traffic signals, **Transportation Research Record 1069**, 1986.

United Kingdom (UK) see Webster and Cobbe [1966].

United States Department of Transportation, Federal Highway Administration [1986] **Manual on Uniform Traffic Control Devices for Streets and Highways**, US. Government Printing Office, 1971 and 1978 as amended 3/1986, pp.4A-1 to 4E-15.

Van As S.C. [1988] **SIMTRA, Road Traffic Simulation Program User Manual**, University of Pretoria, 1978 as amended 1988.

Vodrazka W.C., Lee C.E. and Haenel H.E. [1971] Traffic delay and warrants for control devices, **Highway Research Record 366**, Washington D.C., 1971, pp.79-91.

Wainwright W.S. [1985] Will newly approved warrants result in more signals? **ITE Journal**, December 1985, pp.27-30. (also in **Public Works**, USA, August 1985, pp.72-74.)

Webster, F.V. and Cobbe, B.M. [1966] **Traffic Signals**, Road Research Technical Paper No. 56, Road Research Laboratory, Ministry of Transport, UK, 1966.

APPENDIX D: MISCELLANEOUS REFERENCES

These references were collected during the literature search phase of the *Warrants for Traffic Signals* thesis.

101 Adebisi O. Driver gap acceptance phenomena, **Transportation Engineering Journal**, TE6 vol.168, November 1982, pp.676-688.

102 Akcelik R. Formulae for predicting fuel consumption of cars, **Traffic Engineering Control**, March 1983, pp.115-118.

103 Armour, Mary, The effect of police presence on urban driving speeds, **ITE Journal**, February 1986, pp.40-45.

104 Arnold J.E., Lee R.L. and Ensorff R. Making traffic signals user friendly, **Public Works**, January 1986

105 Australian Road Research Board **Road User Costs and Charges**, Road Technology, Australia circa 1986, pp.575-594.

106 Bang K.L. Optimal control of isolated traffic signals, **Transportation Research Record 597**, TRB, National Academy of Sciences, Washington D.C., 1976, pp.33-35.

107 Beauhien, R.F. Stop signs for speed control?, **Traffic Engineering**, vol.46, no.11, November 1976, p.26.

108 Biggs D.C. and Akcelik R. Models for estimation of car fuel consumption in urban traffic, **ITE Journal**, July 1986, pp.29-32.

109 Brennan, M.J. and Fitzgerald, M.P. A new look at Tanner's formula for the capacity of a minor road at an uncontrolled intersection, **Traffic Engineering and Control**, vol.20, no.4, April 1979, p.220.

110 Chadda H.S. and Carter E.C. Multi-Way Stop signs - Have we gone too far?, **ITE Journal**, May 1983, pp.19-21.

111 Chang M., Evans L., Herman R. and Wasielewski P. Observations of fuel savings due to the introduction of Right-Turn-On-Red, **Traffic Engineering and Control**, October 1977, pp.475-477.

112 Chang M. and Messer C.J. **Guidelines for Installing Traffic Signals at Diamond Interchanges**, Research Report 344-1, Texas Transportation Institute, November 1984.

- 113 Christopherson P.D. and Olafson G.G. Effects of urban traffic control strategies on fuel consumption, **ITE Journal**, November 1978, pp.40-44.
- 114 Cooper, D.F. and Wennell, J. Models of gap acceptance by queues at intersections, **Traffic Engineering and Control**, vol.19, no.4, April 1978, p.178.
- 115 Daryentas J. McDowell M.R.C. and Cooper D.F. Minimum acceptable gaps and conflict involvement in a simple crossing manoeuvre, **Traffic Engineering and Control**, vol.21, no.2, February 1980, p.58.
- 116 Duff, J.T. **Bibliography of Traffic Engineering prepared for Traffic Engineering and Control**, Prentice-Hall Ltd., London, January 1967.
- 117 European Conference of Ministers of Transport **European Rules concerning Road Traffic, Signs and Signals**, ECMT, February 1974.
- 118 Evans L. How does traffic speed affect urban fuel consumption?, Letters to the editor, **ITE Journal**, June 1979, pp.12-13.
- 119 Federal Highway Administration Interim right turn on red national policy, **Traffic Engineering**, September 1976, p.47.
- 120 Federal Highway Administration Stop, Yield and no control at intersections, FHWA Report RD-81/084, **ITE Journal**, February 1982, p.11.
- 121 Ficklin, N.C. For and against semi-actuated traffic signal control, **Traffic Engineering**, vol.43, no.6, March 1973, p.20.
- 122 Flaxman M. and McDougall R. Low cost applications of queueing theory to junction analysis and design, using JUDY, **Traffic Engineering and Control**, vol.21, no.3, March 1980, p.100.
- 123 Galin, D. Left turn on red signal - A matter of controversy, **Australian Road Research**, vol.9, no.4, December 1979, pp.3-10.
- 124 Gern, Richard C. Parking demand at the regionals, **ITE Journal**, September 1978, pp.19-24.
- 125 Gorton D.F. **Road Transport Fuel Savings at Urban Intersections**, National Institute for Transport and Road Research, CSIR, South Africa, February 1978.
- 126 Gorton D.F. **Left Turn On Red**, RR298, NITRR, CSIR, February 1981.

- 127 Greater London Council Findings from the Greater London transportation survey, **Traffic Engineering and Control**, March 1985, pp.178-179.
- 128 Griffiths J.D., Hunt J.G. and Cresswell C. Warrants for Zebra and Pelican crossings using a minimum waiting cost criterion, **Traffic Engineering and Control**, February 1976, pp.59-62.
- 129 Guseman P.K. and Womack K.N. **Measuring Driver Understanding of Traffic Control Devices**, Texas Transportation Researcher, October 1981, pp.10-11.
- 130 Hothersall, D.C. and Salter, R.J. Delays to mixed left and right turning vehicles at priority junctions, **Traffic Engineering and Control**, vol.18, no.2, February 1977, pp.68-74.
- 131 Hunt J. and Williams S. Delays to pedestrians crossing the road at a random point, **Traffic Engineering and Control**, April 1982, pp.216-221.
- 132 ITE Technical Council Committee Yield sign usage and application, **ITE Journal**, October 1978, pp.37-43.
- 133 ITE Technical Council Committee Pedestrian planning activities, **ITE Journal**, June 1986, pp.17-19.
- 134 Jamieson B. and Reid D.A. Managing the performance of junctions in an urban area, **Chartered Municipal Engineer**, vol.100, March 1982, pp.50-56.
- 135 Johannesburg Metropolitan Transportation Study **Initial Interim Transport Plan; Vol.1: Existing Conditions**, Johannesburg, August 1978.
- 136 Joubert H.S. Verkeerbeheermaatregelen, gebruikers- tevredenheid en padveiligheid, **S.A. Nutsdienste**, Februarie 1985, bl.6.
- 137 Jourdain S. Intergreen Timings, **Traffic Engineering and Control**, April 1986, pp.179-182.
- 138 Kell, J.H. Yield signs: Warrants and applications, **Traffic Engineering**, vol.30, no.7, April 1960, p.15.
- 139 Kell, J.H. and Johnson B.C. **Optimizing Street Operations through Traffic Regulations and Control**, NCHRP Report 110, Highway Research Board, 1970.
- 140 Kell, James H. **Urban Intersection Improvements for Pedestrian Safety**, JHK and Associates, July 1975.
- 141 Kell, J.H. and Fullerton, I.J. **Manual of Traffic Signal Design**, Prentice-Hall, 1982.

- 142 Ker I.R. Research into road vehicle operating costs and its application in Australian conditions, **ARR no.77**, Australia, October 1977.
- 143 Khasnabis S., Zegeer C.V. and Cynecki M.J. Effects of pedestrian signals on safety, operations and pedestrian behaviour - Literature review, **Transportation Research Record 847**, 1980, pp.78-86.
- 144 Kunzman, William A. A simplified procedure to determine factors for converting volume counts to ADT's, **Traffic Engineering**, vol.46, no.10, pp.28-30.
- 145 Lin, Feng-Bor Stability and other considerations in simulation analysis of signal control, **Transportation Research Record 956**, 1982, pp.11-18.
- 146 Love G. and True J. An emerging policy on right turn on red, **Traffic Engineering**, November 1976, pp.29-32.
- 147 Maher M.J. and Dowse R.J. Estimating parameters in models of gap acceptance by queues, **Traffic Engineering and Control**, May 1983, pp.252-258.
- 148 McGee H.W. Guidelines for prohibiting right turn on red at signalized intersections, **Transportation Engineering**, January 1978, pp.27-31.
- 149 McGee H.W. Accident experience with right turn on red, BioTechnology Inc., Falls Church, Virginia, **Transportation Research Record**, circa 1975.
- 150 McLean A.J. Accidents at uncontrolled intersections in an urban area, **9th Australian Research Board Conference Proceedings**, vol.9, Part 5, August 1978, pp.161-168.
- 151 Michalopoulos P.G. and Stephanopoulos G. Optimal control of oversaturated intersections, **Traffic Engineering and Control**, May 1978, pp.216-221.
- 152 Municipal Engineer State of the art report: Traffic Management, **Municipal Engineer**, 1984, pp.253-274.
- 153 Municipal Journal Data Sheet Design Standards, **Municipal Journal**, November and December, 1985.
- 154 National Advisory Committee **Traffic Control Devices Handbook**, US Department of Transportation, Federal Highway Administration, 1975.
- 155 NITRR Road User Cost Recovery, **Transport and Road Digest**, National Institute for Transport and Road Research, June 1982.

- 156 NITRR **Fuel Savings Possibilities in Road Transport**, National Institute for Transport and Road Research, Transport Analysis Group, CSIR, Pretoria, 1974.
- 157 NITRR **Traffic Circles**, National Institute for Transport and Road Research, CSIR, August 1984.
- 158 Ohio **Manual of Uniform Traffic Control Devices**, Ohio State, USA, 1972.
- 159 Organization for Economic Cooperation and Development **Driver Behaviour**, OECD Research, June 1970.
- 160 Organization for Economic Cooperation and Development **Automobile Fuel Consumption**, OECD, Paris, December 1981.
- 161 Parry M.H. **Aggression on the Road**, Tavistoch Publications, 1968.
- 162 Petersen, N.J. and Samdahl, D.R. **Highway Traffic Data for Urbanized Area Project Planning and Design**, NCHRP Report 255, Transportation Research Board, Washington D.C., December 1982.
- 163 Peterson, B.E. Calculation of capacity, queue length and delay in road traffic facilities, **Traffic Engineering and Control**, vol.18, no.6, June 1977, p.310.
- 164 Plank A.W. A general capacity formula for an uncontrolled intersection, **Traffic Engineering and Control**, June 1984, pp.327-329.
- 165 Polus A. Gap acceptance characteristics at unsignalized urban intersections, **Traffic Engineering and Control**, May 1983.
- 166 Polus A. Driver behaviour and accident record at unsignalized urban intersections, **Accident Analysis and Preview**, USA, 1985, pp.25-32.
- 167 Pontier W.E., Miller P.W. and Kraft W.H. **Optimizing Flow on Existing Street Networks**, NCHRP Report 113, Highway Research Board, 1971.
- 168 Pretorius H.B. **Stop/Yield Sign: Final Report**, RY/2/83, NITRR, CSIR, English version 1985.
- 169 Pretty R.L. Traffic signal calculations in relation to junction layout, capacity and delay, **Traffic Engineering and Control**, vol.21, no.3, March 1980, p.110.

- 170 Ramsey J.B.H. and Routledge I.W. A new approach to the analysis of gap acceptance times, **Traffic Engineering and Control**, vol.15, no.7, November 1973, pp.355-357.
- 171 Rankin W.W. 1984 Urban transportation/traffic engineering agency functions and administration study - Part II, **ITE Journal**, December 1985, pp.23-26.
- 172 Richardson, Anthony J. A delay model for multiway Stop-sign intersections, **Transportation Research Record 1112**, 1986, pp.107-114.
- 173 Ryan T.A. and Davis C.F. **Driver Use of All Red Signal Interval**, Transportation Research Record 881, 1982.
- 174 Salter R.J. Some effects of lag and gap acceptance distribution on average delay at priority intersections, **Traffic Engineering and Control**, August 1970, pp.178-181.
- 175 Sampson J.D. **Traffic Counting Program Carried Out by the City Engineer's Department, Johannesburg**, Road Planning and Traffic Engineering, City of Johannesburg, 1977.
- 176 Sampson J.D. Thoughts on the future of traffic signal indications, **Proceedings of the Annual Transportation Convention**, Pretoria, 1987.
- 177 Sampson, J.D. Traffic Signals: General, **Seminar on New Traffic Signs presented under the auspices of the CSRA/CUTA Road Signs Subcommittee**, Pretoria, 16-18 May, 1988.
- 178 Skinner D.G. **Report on Traffic Signals and Control Methods in Durban**, City Engineer's Department, Johannesburg, February 1975.
- 179 Somerfeld W.O. Pedestrian control at signalized intersections, Letters to the Editor, **ITE Journal**, June 1986, pp.4-5.
- 180 Sosin, J.A. Delays at intersections controlled by fixed cycle traffic signals, **Traffic Engineering and Control**, vol.21, no.8/9, August/September 1980.
- 181 Spitz S. Gap based criteria for signal warrants, Letters to the Editor, **ITE Journal**, August 1985, pp.50-51.
- 182 Taylor I.G., Bell M. and Geary G.M. Queue volume: A measure of congestion, **Traffic Engineering and Control**, November 1987, pp.582-585.
- 183 Todd, K. Modern Rotaries, **ITE Journal**, vol.49, no.7, July 1979, p.12.

- 184 Tolle, J.E. **Vehicular Headway Distributions: Testing and Results**, Transportation Research Institute, Carnegie-Mellon University, 1971.
- 185 Tomecki A.B. **A simplified Technique for Evaluating Traffic Signal Effectiveness**, RT/22/79, National Institute for Transport and Road Research, CSIR, South Africa, April 1978.
- 186 Tomecki A.B. **Vehicle Actuated Signal Control: A Study of an Isolated Intersection in Pretoria**, RT/6/79, National Institute for Transport and Road Research, CSIR, South Africa, February 1979.
- 187 Transportation and Road Research Laboratory **Predicting Traffic Peak Shapes from Hourly Flow Counts**, TRRL Suppl. Report 765, June/July 1983, p.325.
- 188 TRB **Traffic Control Devices, 1983**, Transportation Research Record 926, Washington D.C., 1983.
- 189 TRB Developments in traffic signal systems, **Transportation Research Circular 282**, July 1984.
- 190 TRB **Traffic Signal Systems**, Transportation Research Record 1057, Washington D.C., 1986.
- 191 Troutbeck R.J. **Capacity and Delays at Roundabouts - A Literature Review**, Australian Road Research Board 14(4), December 1984, pp.205-216.
- 192 Uber C.B. Comparison of acceptance of gaps and lags, **Proceedings The Ninth Australian Road Research Board Conference**, vol.9, Brisbane, August 1978.
- 193 United States Department of Transportation, **Traffic Control Devices: An Operating Guide**, NAC, FHWA, 1975.
- 194 Upchurch J.E. [1983] Guidelines for use of sign control at intersections to reduce energy consumption, **ITE Journal**, January 1983, pp.22-34.
- 195 Virkler M. **Pedestrian Flows at Signalized Intersections**, Transportation Research Record 847.
- 196 Wagner F.A., Barnes F.C. and Gerlough D.L. **Improved Criteria for Traffic Signal Systems in Urban Networks**, NCHRP Report 124, Highway Research Board, 1971.
- 197 Zegeer C.V., Opiela K. and Cynecki M. Effect of pedestrian signals and signal timing on pedestrian accidents, **Transportation Research Record 847**, 1980, pp.62-77.